

## Declaration of Performance

No. 37021-04 Valid from 08/09/2020

1. type

2. Intended use

## RT562FF UNIKA EOS SOFT-MOULDED Varenr. 3 554 05 00

 $oldsymbol{\mathsf{U}}$  Bricks for use in unprotected masonry

		<u> </u>		
3. Manufacturer	Randers Tegl A/S, HAMMERSHØJ TINDBÆKVEJ 16 8830 TJELE	TEGLVÆRK		
4. System of AVCP	2+	2+		
5. Notified body	factory production control and the	Dancert A/S with identification no. 1073 performed the initial inspection of the manufacturing plant and of factory production control and the continuous surveillance, assessment and evaluation of factory under system 2+ and issued the certificate of conformity of the factory production control with the no.1073-CPR-M199		
6. Declared performance:				
Essential characteristics:		Performance	Harmonized technical standard	
Dimensions, [mm]:	Length	228		
	Width	108		
	Height	40		
Tolerance, [mm]	T2	L±4 B±3 H±2		
Range, [mm]	Rm	L 9, B 5, H 3		
Configuration	Shape and features	Massive		
	EN1996-1-1	G1		
Compressive strength [N/mm2]	Category	1	22	
	average, min	60	201	
	normalized, min	45	A1 ::	
	Direction of load	Perpendicular to bed faces	<del></del>	
Dimensional stability		NPD	EN771-1:2011+A1:2015	
Bond strength		NPD		
Active soluble salts content (Category)		S2		
Reaction to fire		A1		
Water absorption Maximum Weight%		12		
Water vapour permeability		NPD		
Direct airborne sound insulation [kg/m²]	Gross density	1800		
	Tolerance ± 10 %	D1		
Thermal resistance		NPD		
Durability against freeze/thaw		F2		

7. The performance of the product identified above is in conformity with the set of declared performances. This declaration of performance is issued under the sole responsibility of the manufacturer identified above. Signed for and on behalf of the manufacturer by:

NPD

Kresten Ejlskov Hansen, Teknisk Direktør

Signature

08/09/2020

Dangerous substances